

Sunshine Home Material Cabinetry · Stone · Flooring

Value Quality Factory Direct

SAWATCH SPC FLOORING SPECIFICATIONS

PRODUCT INFORMATION

CONSTRUCTION Engineered Rigid Core Stone-Polymer Composite (SPC) with 20mil (0.5mm) Wear Layer

PLANK DIMENSIONS 7/32" Thick x 7-7/32" Wide x 48-1/32" Long (attached 1.5mm EVA pad)

MILLING 4 sided Micro-Bevel Edge / Uniclic® Locking System **FINISH** Aluminer™ UV Cured Acrylic / 10% Sheen / Textured

COLOR VARIANCE

INSTALLATION Floating. Radiant floor heating compatible. Above, on, or below grade.

ALUMINER™

ENVIRONMENTAL FloorScore® Certified / 100% Virgin PVC

100% waterproof and safe to install in full bathrooms, laundry rooms, and mudrooms. WATER PERFORMANCE

PACKAGING

BOX WEIGHT: 50 LBS PACK SIZE: 40 Boxes/Pallet BOX DIMENSIONS: 3" x 8" x 49"

(2 LAYERS OF PROTECTIVE COATING)

20MIL (0.5MM)

WEAR LAYER

DECOR FILM

RIGID CORE SPC

1.5MM EVA PAD

PLANKS PER BOX: 12 SQFT PER BOX: 28.84

WARRANTY

FINISH 50-year Residential / 15-year Light Commercial

STRUCTURE Lifetime Structural Warranty



CIMARRON 55643




SAGAUCHE 55645



KEYSTONE 55647



SOMERSET 55649



TEXTURED

TEXTURED

SILVERTHORNE 55651



TEXTURED

TEXTURED JUNIPERO 55660



TEXTURED OBISPO 55661

TEXTURED



TEXTURED



LOMA 55662